


1600-B SLIDING DOOR ROLLER REPLACEMENT

- 1. OPEN DOOR PART WAY,
- 2. REMOVE RETAINER CHANNEL (SEE FIG. A)
- 3. REMOVE DOOR BY LIFTING UP AND PULLING BOTTOM OF DOOR OUT AND DOWN TO REMOVE
- 4. WITH DOOR REMOVED FROM FRAME, YOU CAN REPLACE THE ROLLERS AND GLIDES (SEE FIG. B)

RE-INSTALLING DOOR

- 5. RE-INSTALL DOOR BY INSERTING DOOR HEAD INTO HEADER CHANNEL THEN SWINGING DOOR BOTTOM INWARD TO SET ROLLERS ON SILL TRACK.
- 6. RE-INSTALL RETAINING CHANNEL, SCREW IN PLACE

NOTE: GREASE THE ROLLERS AT LEAST ONCE A YEAR WITH A QUALITY MARINE GRADE GREASE TO ENSURE SMOOTH AND TROUBLE—FREE OPERATION OF ROLLERS



1-3/8" DIA. ROLLERS ~ 2 EA.

DELRIN GLIDES ~ 2 EA.

USE 601-0008 ROLLER ASSY. FOR 1600-B DOORS

	A^{LUMII}_{2000}	IN O IM	595 E. OREGON RD. LITITZ, PA 17543 717 569-2300			
	CUSTOMER:					
	1600-B SLIDING DOOF				QUANTITIY/BOA 1 EA	
I.D. NO.	1600-B	SCALE: 1 ; 8	DJM	DATE;	/30/0)1
REV.	DRAWING NAME;				PAGE	
	ROLLER	ROLLER REPLACMENT			1 OF	1